

DR680

The **RIEGL® DR680** is the accompanying **Digital Data Recorder** to the state-of-the-art **RIEGL Airborne Laser Scanners**, using **three removable drive carriers with integrated Solid State Drives** for smooth operation.

Providing various data interfaces the DR680 is universally suited to store data acquired with the full waveform laser scanners **RIEGL LMS-Q560** and **LMS-Q680(i)** as well as with the **RIEGL's** new online-waveform processing V-line laser scanners.

Using solid state drives increases the reliability in harsh environment and at high flying altitudes. These drives are hot-swappable and allow immediate access to data already acquired, ready to be analyzed on the fly or in the office, while the system is still in operation finishing the surveying mission. Data rates of up to 80 MBytes/sec guarantee uninterrupted storage of data covering the requirements of actual and future generations of **RIEGL** high speed laser scanners. Additionally an online data integrity check is performed prior transferring the scan data to the solid state drives.

Solid State Drives (SSD) 3 x 2.5"

Removable drive carriers

Up to 10 hours airborne data logging capacity

Input data rate up to 80 MByte/sec

High data download rate up to 100 MByte/sec

Online data integrity check

Specified for a flight altitude up to 18,000 ft




visit our website www.riegl.com



RIEGL®
LASER MEASUREMENT SYSTEMS

Dimensional Drawings *RIEGL* DR680



Technical Data *RIEGL* DR680

Data Recorder Performance

Storage Capacity	3 x 240 GByte ³⁾
Data Rate (Input)	up to 80 MByte/sec
Logging Capacity ¹⁾	typically 10 h
Data Rate (Output) ²⁾	up to 100 MByte/sec

1) at 200 kHz laser pulse repetition frequency of the LMS-Q680 scanner, 2 targets (200 Bytes/measurement), 45° scan angle

2) removable hard disk in mounting frame with SATA interface on up to date PC

3) Subject to rapid technical change, storage capacity of Solid State Drives may differ from values given at the time of datasheet's issue.

Data Interfaces

Input Interface

2 x High Speed Serial Data Link
2 x Small Form-Factor Pluggable Transceiver (SFP)
GigE-LAN

Output Interface

SATA on removable drive carrier
GigE-LAN
USB

General Technical Data

Power Supply	18 - 32 V DC
Current Consumption	approx. 0.8 A @ 24 V DC
Main Dimension (L x W x H)	307 x 276 x 113 mm
Weight	approx. 6.1 kg (3 drive carriers included)
Max. Flight Altitude	18 000 ft (5 500 m) above MSL
Temperature Range	0°C up to +40°C (operation) / -10°C up to +50°C (storage)



RIEGL[®]
LASER MEASUREMENT SYSTEMS

RIEGL Laser Measurement Systems GmbH, 3580 Horn, Austria
Tel.: +43-2982-4211, Fax: +43-2982-4210, E-mail: office@riegl.co.at

RIEGL USA Inc., Orlando, Florida 32819, USA
Tel.: +1-407-248-9927, Fax: +1-407-248-2636, E-mail: info@rieglusa.com

RIEGL Japan Ltd., Tokyo 1640013, Japan
Tel.: +81-3-3382-7340, Fax: +81-3-3382-5843, E-mail: info@riegl-japan.co.jp

www.riegl.com